



Reviewed on 01/01/2017

## Safety Data Sheet

**WARNING: PRODUCT COMPONENTS PRESENT HEALTH AND SAFETY HAZARDS. READ AND UNDERSTAND THIS MATERIAL SAFETY DATA SHEET (M.S.D.S.). ALSO, FOLLOW YOUR EMPLOYER'S SAFETY PRACTICES.**

The information contained herein relates only to the specific product. If the product is combined with other materials, all component properties must be considered. **BE SURE TO CONSULT THE LATEST VERSION OF THE MSDS. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE FROM HARRIS PRODUCTS GROUP** Harris Products Group, HGE PTY LTD, Brisbane | Melbourne | Perth | New Zealand, 14 Queensland Rd, Darra, QLD 4076, Phone: (07) 3375 3670 | Fax: (07) 3375 3620, Email: sales@hgea.com.au, www.harrisproductsgroup.com.au,

### STATEMENT OF LIABILITY-DISCLAIMER

To the best of the Harris Products Group knowledge, the information and recommendations contained in this publication are reliable and accurate as of the date prepared. However, accuracy, suitability, or completeness are not guaranteed, and no warranty, guarantee, or representation, expressed or implied, is made by Harris Products Group. as to the absolute correctness or sufficiency of any representation contained in this and other publications; Harris Products Group assumes no responsibility in connection therewith; nor can it be assumed that all acceptable safety measures are contained in this and other publications, or that other or additional measures may not be required under particular or exceptional conditions or circumstances. Data may be changed from time to time.

---

## 1 IDENTIFICATION

### Product identifier

**Trade name:** Chemical Sharpener for Tungsten Points

**Product size:** Variable

**Other means of identification:** None

**SDS Number:** No other identifiers

### Recommended use and restriction on use

**Recommended use:** Chemically sharpens tungsten electrodes

**Restrictions on use:** No further relevant information available.

### Manufacturer/Importer/Supplier/Distributor information

#### Importer:

Harris Products Group

14 Queensland Rd

Darra, QLD, Australia 4076

(07) 33753670

**Safety Data Sheet Questions:** sales@hgea.com.au

**Arc Welding Safety Information:** [www.lincolnelectric.com/safety](http://www.lincolnelectric.com/safety)

### 24-Hour Emergency Response Telephone Numbers:

000 - Australia

111 - New Zealand

**3E Company Access Code:** 333895

---

## 2 HAZARD(S) IDENTIFICATION

### EMERGENCY OVERVIEW

WHITE TO SLIGHTLY YELLOW CRYSTALLINE SOLID. TOXIC IF SWALLOWED OR DUST IS INHALED. OXIDIZER: MAY IGNITE ORGANIC MATERIALS AND REACT WITH OTHER MATERIALS. CAN DECOMPOSE IF MIXED WITH ACIDS OR EXPOSED TO FIRE CONDITIONS, RELEASING TOXIC NITROGEN OXIDES.

**GHS classification of the substance/mixture.**

Classified according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

**Classification of the substance or mixture**

The product is classified as hazardous according to the Globally Harmonized System (GHS).

**Potential Health Affects**

**SKIN:** May cause skin irritation.

**EYES:** May strongly irritate or burn the eyes.

**INHALATION:** Product mists may cause irritation to the respiratory tract.

**INGESTION:** May irritate the gastrointestinal tract. Although small quantities are used in food preparation, swallowing moderate amounts of sodium nitrite can result in serious toxic effects including death. Effects include nausea, weakness, cyanosis (blue skin), collapse and coma, possibly leading to death. Sodium nitrite interferes with the blood's ability to transport oxygen.

**DELAYED EFFECTS:** None known. If sodium nitrite is used with amines found in certain cutting fluids, potentially carcinogenic nitrosamine compounds may be formed.

**3 Composition/information on ingredients****Chemical characterization: Mixtures**

**Description:** Mixture of the substances listed below with nonhazardous additions

Dangerous components:		
CAS	Name	Proportion
7632-00-0	Sodium Nitrite	>98%

**Additional information:**

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

**Composition comments:**

The term "Hazardous Ingredients" should be interpreted as a term defined in Hazard Communication standards and does not necessarily imply the existence of a hazard. The product may contain additional nonhazardous ingredients or may form additional compounds under the condition of use. Refer to Sections 2 and 8 for more information.

**4 First-aid measures****Description of first aid measures**

**EYE CONTACT:** Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.

**SKIN CONTACT:** Flush with plenty of water, removing contaminated clothing. If irritation develops, get medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get prompt medical attention.

**INGESTION:** Do not induce vomiting. Immediately give large quantities of water. Get medical attention immediately.

**NOTES TO PHYSICIAN:** Sodium nitrite forms methemoglobin in the blood stream. Treat accordingly.

## 5 Fire-fighting measures

### Flammable Properties

**FLASH POINT:** Not Flammable

**FLASH POINT METHOD:** Not Applicable

**AUTOIGNITION TEMPERATURE:** Not Applicable

**UPPER FLAME LIMIT (VOLUME % IN AIR):** Not Applicable

**LOWER FLAME LIMIT (VOLUME % IN AIR):** Not Applicable

**FLAME PROPAGATION RATE (SOLIDS):** Not Applicable

**OSHA FLAMMABILITY CLASS:** Not Applicable

**SUITABLE EXTINGUISHING MEDIA:** Use flooding amounts of water or other agents.

**UNSUITABLE EXTINGUISHING MEDIA:** Do not use dry chemicals containing ammonium phosphate.

Explosion Limits

**HAZARDOUS COMBUSTION PRODUCTS:** No information available

**IMPACT SENSITIVITY:** No information available

**SENSITIVITY TO STATIC DISCHARGE:** No information available

**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:** Material does not burn but is an oxidizing agent and will support combustion of other materials. Product decomposes above 608°F releasing toxic nitrogen oxides.

**PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:** Wear self-contained breathing apparatus and full protective equipment.

### Additional information

Read and understand the Work Safe Australia Code of Practice on Welding Processes and “Standard for Fire Prevention During Welding, Cutting and Other Hot Work” before using this product. Section 274 of the Work Health and Safety Act (the WHS Act.)

## 6 Accidental release measures

**IN CASE OF SPILL OR OTHER RELEASE:** Remove sources of ignition. Ventilate area. Use non-sparking tools and equipment. Sweep or shovel spilled material into containers. Dispose of material according to local authorities. Do not allow product or residues to enter waterways and/or any source of drinking water.

### Methods and material for containment and cleaning up:

Clean up spills immediately, observing precautions in the personal protective equipment in Section 8. Prevent product from entering any drains, sewers or water sources.

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

### Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

**HANDLING:** Avoid contact with skin and eyes. Do not breathe product dusts. Avoid contact with incompatible, combustible, organic or readily oxidizable materials.

**STORAGE:** Store in a cool, dry, well-ventilated area. Keep containers tightly closed. Do not store on wooden floors. Isolate from combustible materials. Empty containers may contain product residues; observe all warnings and precautions listed for the product.

Read and understand the manufacturer's instruction and the precautionary label on the product. Refer to Lincoln Safety Publications at [www.lincolnelectric.com/safety](http://www.lincolnelectric.com/safety). See the Australian Standard - AS 1674.1 – 1997 – Reconfirmed 2016. Safety in Welding and Allied Processes Australia.

## 8 Exposure controls/personal protection

**Additional information about design of technical systems:** No further data; see item 7.

### Control parameters

#### Exposure Guidelines:

Refer to the Safe Environments risk management document – Welding Fume -

<http://www.safeenvironments.com.au/welding-fume/> The exposure standard refers to the publication by Work Safe Australia “Workplace Exposure Standard for Airborne Contaminants” with the Date of Effect being 22 December 2011. Work Safe Australia note that “exposure standards do not represent a fine dividing line between a healthy and unhealthy work environment. Natural biological variation and the range of individual susceptibilities mean that a small number of people might experience adverse health effects below the exposure standard.

The American Governmental Congress of Industrial Hygienists (ACGIH) however recommends a Threshold Limit Value (TLV) Time Weighted Average (TWA) of 5 mg/m<sup>3</sup> for welding fume, on the assumption that there are no highly toxic constituents. However, in Australia, there is no specific exposure standard for welding fume. This is due to the fume being a combination of the metals and filler material being molten together along with cleaning and fluxing agents present. Each metal or material within the process of welding will generally have its own exposure standard.

7632-00-0	Sodium Nitrite	TWA 2 mg/m <sup>3</sup>
-----------	----------------	-------------------------

Refer to Worksafe Australia for standards:

[http://www.safeworkaustralia.gov.au/sites/SWA/about/Publications/Documents/639/Workplace\\_Exposure\\_Standards\\_for\\_Airborne\\_Contaminants.pdf](http://www.safeworkaustralia.gov.au/sites/SWA/about/Publications/Documents/639/Workplace_Exposure_Standards_for_Airborne_Contaminants.pdf)

### Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Do not eat, drink or smoke when using the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. Personal air monitoring is generally undertaken over a representative period of time undertaken to Australian Standard AS 3640-2009 Workplace atmospheres – Method for sampling and gravimetric determination of inhalable dust using IOM sampling heads with flow rate of 2.0 L/min.

Keep away from foodstuffs, beverages and feed.

#### Engineering controls:

##### Ventilation

Use enough ventilation, local exhaust at the the flame or heat source, or both to keep the fumes and gases from the worker's breathing zone and the general area. Train the operator to keep his head out of the fumes. Keep exposure as low as possible.

#### Breathing equipment:

Keep your head out of fumes. Use enough ventilation and local exhaust to keep fumes and gases from your breathing zone and the general area. An approved respirator should be used unless exposure assessments are below applicable exposure limits.

#### Protection of hands:



Thermally-protective gloves.

Suitable gloves can be recommended by the glove supplier.  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Eye protection:**



Wear chemical safety goggles. Do not wear contact lenses

**Body protection:** Protective work clothing

## 9 Physical and chemical properties

### Information on basic physical and chemical properties

#### General Information

**Appearance:**

<b>Form:</b>	Crystals
<b>Colour:</b>	White to slightly yellow
<b>Odour:</b>	Odourless
<b>Odour Threshold:</b>	Not Determined
<b>pH-value:</b>	~9.0 (for aqueous solution)

**Change in condition**

<b>Melting point/Melting range:</b>	520°F
<b>Boiling point/Boiling range:</b>	Decomposes above 608 °F

<b>Flash point:</b>	Not Flammable
<b>Flammability (solid, gaseous):</b>	Not Determined
<b>Auto-ignition temperature:</b>	Not Applicable
<b>Decomposition temperature:</b>	Not Determined
<b>Auto igniting:</b>	Not Applicable
<b>Danger of explosion:</b>	No Information Available

**Explosion Limits:**

<b>Lower:</b>	Not Determined
<b>Upper:</b>	Not Determined

<b>Vapour Pressure:</b>	Not Applicable
<b>Density:</b>	Not Applicable
<b>Relative Density:</b>	Not Applicable
<b>Vapour Density:</b>	Not Applicable
<b>Evaporation Rate:</b>	Not Determined

**Solubility in/Miscibility with water:** 80.8 g/100 g at 68°F

<b>Partition coefficient (n-octanol/water):</b>	Not information applicable
<b>Viscosity:</b>	Not information applicable
<b>Dynamic:</b>	Not applicable
<b>Kinematic:</b>	Not applicable
<b>Other Information:</b>	No further relevant information available

## 10 Stability and reactivity

**CHEMICAL STABILITY:** Normally stable.

**CONDITIONS TO AVOID:** Material slowly oxidizes to sodium nitrite when exposed to air. Avoid heat, flame, ignition sources, shock, friction and incompatibilities.

**INCOMPATIBLE PRODUCTS:** Hazardous reactions can occur with acids, ammonium compounds, reducing agents (particularly cyanides, thiocyanates and thiosulfates). May ignite organic compounds and other combustible materials.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of nitrogen (toxic and irritating).

**POSSIBILITY OF HAZARDOUS REACTIONS:** Will not occur.

### **Hazardous decomposition products:**

Brazing fumes and gases cannot be classified simply. The composition and products: quantity of both are dependent upon the metal being joined, the process, procedure and filler metals and flux used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being joined (such as paint, plating, or galvanizing), the number of operators and the volume of the worker area, the quality and amount of ventilation, the position of the operator's head with respect to the fume and fumes from chemical fluxes used in some brazing operations. When the wire or rod is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc., as noted above.

---

## 11 Toxicological information

**IRRITATION:** No information available

**CORROSIVITY:** No information available

**SENSITIZATION:** No information available

### **Chronic Toxicity**

**CARCINOGENICITY:** There are no known carcinogenic chemicals in this product.

**MUTAGENIC EFFECTS:** No information available

**REPRODUCTIVE EFFECTS:** No information available

**DEVELOPMENTAL EFFECTS:** No information available

**TERATOGENICITY:** Multiple reproductive tests indicate that sodium nitrite is not teratogenic.

**TARGET ORGAN EFFECTS:** No information available

**OTHER ADVERSE EFFECTS:** Fetal toxicity has been demonstrated in pregnant animals fed toxic doses of sodium nitrite. This is due to the formation of methemoglobin.

**ENDOCRINE DISRUPTOR INFORMATION:** No information available

---

## 12 Ecological information

### Ecotoxicity

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**PERSISTENCE AND DEGRADABILITY:** No information available

**BIOACCUMULATION:** No information available

**MOBILITY IN ENVIRONMENTAL MEDIA:** No information available

**Other adverse effects** No further relevant information available.

## 13 Disposal considerations

**WASTE DISPOSAL METHODS:** Dispose of waste in accordance with all state and local regulations.

**CONTAMINATED PACKAGING:** Empty containers should be taken for local recycling, recovery or waste disposal.

## 14 Transport Information

UN-Number DOT, ADR, ADN, IMDG, IATA	Not Regulated
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Not Regulated
Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA Class	Not Regulated
Packing group DOT, ADR, IMDG, IATA	Not Regulated
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable.

## 15 Regulatory information

### Product Name: **Chemical Sharpener for Tungsten Points**

Refer to the Australian Inventory of Chemical Substances – AICS at <https://www.nicnas.gov.au/chemicals-on-AICS#main>

**Poison schedule:** Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). <https://www.legislation.gov.au/Details/F2016L01638>

**Classifications:** Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

## 16 Other information

### References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice

Standard for the Uniform Scheduling of Medicines and Poisons

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Modell Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work, Australia

American Conference of Industrial Hygienists (ACGIH)

Globally Harmonised System of classification and labelling of chemicals.

**WELDING (1):** Due to the diversity of welding techniques, processes, materials used, nature of the surface being welded and the presence of contaminants, the fumes & gases associated with welding will vary in composition and quantity. When assessing a welding process, the toxic fumes generated may not only be associated with the parent metal, filler wire or electrode. The welding/cutting arc may generate nitrogen oxides, carbon monoxide & other gases, whilst UV radiation emitted from some arcs generates ozone. Ozone may irritate mucous membranes and cause pulmonary oedema & haemorrhage. Shielding gases (e.g. carbon dioxide and inert gases i.e. argon and helium) in high concentrations, in confined spaces, may reduce oxygen in the atmosphere to dangerous levels, resulting in possible asphyxiation.

**WELDING (2):** In addition to complying with individual exposure standards for specific contaminants, where current manual welding processes are used, the fume concentration inside the welder's helmet should not exceed 5 mg/m<sup>3</sup> ( unless otherwise classified) when collected in accordance with Australian Standard AS 3853.1: Fume from welding and allied processes - Guide to methods for the sampling and analysis of particulate matter and AS 3853.2: Fume from welding and allied processes - Guide to methods for the sampling and analysis of gases. Airway irritation and metal fume fever are the most common acute effects from welding fumes. Reported to cause reduced sperm quality in welders.

**WELDING (3):** Other gases and fumes associated with welding processes include: Inert shielding gases (e.g. argon, carbon dioxide, helium) which may reduce the atmospheric oxygen content in poorly ventilated areas. UV-radiation and Infra-Red radiation may decompose chlorinated degreasing agents to form highly toxic and irritating phosgene gas. This may occur if a metal has been degreased but inadequately dried or when vapours from a nearby degreasing bath enter the welding zone.

**WELDING (4):** Welding fumes may contain a wide variety of chemical contaminants, including oxides and salts of metals and other compounds which may be generated from electrodes, filler wire, flux materials and from the welded material (e.g. painted surfaces). Welding stainless-steel and its alloys generates nickel and chromium (VI) compounds. Welding fumes are retained in the lungs. Sparingly soluble compounds may be released slowly from the lungs. Welding fume is classified as possibly carcinogenic to humans (IARC Group 2B).

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:



The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**Disclaimer:**

We urge each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product.

Harris Products Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

[ End of SDS ]